

# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### PRODUCT PHOTOGRAPH




### GENERAL INFORMATION

Product Code	<b>62000</b>
Product Category	<b>Downlights-Gu10</b>
Product Family	<b>Mea</b>
Mounting Location	<b>Ceiling</b>
Application Environment	<b>Indoor</b>

### DIMENSION & WEIGHT

LxWxH (cm)	<b>D: 5 H: 6 cm</b>
Cut out (cm)	<b>N/A</b>
Weight (Kgr)	<b>N/A</b>

### TECHNICAL DRAWING



### MATERIAL & COLOR

Product Color	<b>White</b>
Body Material	<b>Aluminium</b>
Cover Material	<b>N/A</b>

### APPLICATION & MOUNTING

Ambient Working Temp.	<b>45 C</b>
Type of Protection	<b>IP20</b>
Protection Class IK	<b>IK03</b>
Dimmable	<b>Yes</b>
Type of Dimming (Optional)	<b>Triac/Dali</b>
Mounting type	<b>Recessed</b>
Mounting Depth (cm)	<b>Ceiling</b>
Led Module Replaceable	<b>No</b>
Light Source	<b>Led</b>
Adjustable	<b>No</b>

### COMPATIBLE WITH

— On/Off Driver: 9011763, 6001, 64001

— Triac Driver: 9844019

— Dali Driver: 9621523

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com



# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### ELECTRICAL DATA

Power (Nominal)	<b>9</b>
Input voltage (Nominal)	<b>36Vdc</b>
Mains Frequency	<b>50/60Hz</b>
Output voltage	<b>36Vdc</b>
Output Current	<b>250mA</b>
Power Factor	<b>0,82</b>
Efficiency	<b>&gt;80%</b>
SVM	<b>&lt;0.4</b>
Pst	<b>&lt;1</b>
Class	<b>III</b>

### PHOTOMETRICAL DATA

Luminous Flux	<b>800</b>
Luminous Efficacy	<b>88.9</b>
Color Temperature	<b>3000</b>
Light Color (Designation)	<b>Warm White</b>
CRI	<b>&gt;90</b>
SDCM	<b>&lt;3</b>
Beam Angle	<b>N/A</b>
UGR	<b>N/A</b>

### LIFESPAN

Lifetime	<b>50000</b>
----------	--------------

### CERTIFICATES

Certificates	<b>CE, UKCA</b>
--------------	-----------------

### WARRANTY

Warranty	<b>5 Years</b>
----------	----------------

### LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com

