

# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### PRODUCT PHOTOGRAPH




### GENERAL INFORMATION

|                         |                  |
|-------------------------|------------------|
| Product Code            | 9058106          |
| Product Category        | Ceiling-Led      |
| Product Family          | Perfect Profiles |
| Mounting Location       | Ceiling          |
| Application Environment | Indoor           |

### DIMENSION & WEIGHT

|              |                |
|--------------|----------------|
| LxWxH (cm)   | D: 60 H: 10 cm |
| Cut out (cm) | N/A            |
| Weight (Kgr) | N/A            |

### TECHNICAL DRAWING



### MATERIAL & COLOR

|                |           |
|----------------|-----------|
| Product Color  | Black     |
| Body Material  | Aluminium |
| Cover Material | N/A       |

### APPLICATION & MOUNTING

|                            |                         |
|----------------------------|-------------------------|
| Ambient Working Temp.      | 45 C                    |
| Type of Protection         | IP20                    |
| Protection Class IK        | IK03                    |
| Dimmable                   | Yes                     |
| Type of Dimming (Optional) | Dimming With Controller |
| Mounting type              | Surface                 |
| Mounting Depth (cm)        | Ceiling                 |
| Led Module Replaceable     | No                      |
| Light Source               | Led                     |
| Adjustable                 | No                      |

### COMPATIBLE WITH

— On/Off Driver: N/A

— Triac Driver: N/A

— Dali Driver: N/A

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com



# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### ELECTRICAL DATA

|                         |                   |
|-------------------------|-------------------|
| Power (Nominal)         | <b>40</b>         |
| Input voltage (Nominal) | <b>220-240Vac</b> |
| Mains Frequency         | <b>50/60Hz</b>    |
| Output voltage          | <b>N/A</b>        |
| Output Current          | <b>N/A</b>        |
| Power Factor            | <b>N/A</b>        |
| Efficiency              | <b>N/A</b>        |
| SVM                     | <b>N/A</b>        |
| Pst                     | <b>N/A</b>        |
| Class                   | <b>I</b>          |

### PHOTOMETRICAL DATA

|                           |                  |
|---------------------------|------------------|
| Luminous Flux             | <b>2000</b>      |
| Luminous Efficacy         | <b>50</b>        |
| Color Temperature         | <b>2700-6000</b> |
| Light Color (Designation) | <b>Ww - Cw</b>   |
| CRI                       | <b>&gt;80</b>    |
| SDCM                      | <b>&lt;3</b>     |
| Beam Angle                | <b>120</b>       |
| UGR                       | <b>N/A</b>       |

### LIFESPAN

|          |              |
|----------|--------------|
| Lifetime | <b>50000</b> |
|----------|--------------|

### CERTIFICATES

|              |                 |
|--------------|-----------------|
| Certificates | <b>CE, UKCA</b> |
|--------------|-----------------|

### WARRANTY

|          |                |
|----------|----------------|
| Warranty | <b>5 Years</b> |
|----------|----------------|

### LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com

