

NOVA LUCE

PRODUCT DATASHEET

Version: 001

PRODUCT PHOTOGRAPH




GENERAL INFORMATION

Product Code	9540306
Product Category	Downlights-Commercial
Product Family	Spark
Mounting Location	Ceiling
Application Environment	Outdoor

DIMENSION & WEIGHT

LxWxH (cm)	D:14.5 H:6.5
Cut out (cm)	12,5
Weight (Kgr)	N/A

TECHNICAL DRAWING



MATERIAL & COLOR

Product Color	White
Body Material	Aluminium
Cover Material	N/A

APPLICATION & MOUNTING

Ambient Working Temp.	45 C
Type of Protection	IP54
Protection Class IK	IK04
Dimmable	Yes
Type of Dimming (Optional)	Triac/Dali
Mounting type	Recessed
Mounting Depth (cm)	Ceiling
Led Module Replaceable	No
Light Source	Led
Adjustable	No

COMPATIBLE WITH

— On/Off Driver: Included

— Triac Driver: 9844002, 9540319

— Dali Driver: 9621523

NOVA LUCE S.A

Schimatari Viotias
32009, Greece

+30 22620 58 121
+30 22620 56 743

info@novaluce.com
www.novaluce.com



NOVA LUCE

PRODUCT DATASHEET

Version: 001

ELECTRICAL DATA

Power (Nominal)	18
Input voltage (Nominal)	220-240Vac
Mains Frequency	50/60Hz
Output voltage	40Vdc
Output Current	450mA
Power Factor	0,9
Efficiency	ò88%
SVM	?0.4
Pst	?1
Class	II

PHOTOMETRICAL DATA

Luminus Flux	2003
Luminous Efficacy	111.3
Color Temperature	4000
Light Color (Designation)	Neutral White
CRI	>90
SDCM	<3
Beam Angle	60
UGR	N/A

LIFESPAN

Lifetime	50000
----------	--------------

CERTIFICATES

Certificates	CE ROHS
--------------	----------------

WARRANTY

Warranty	5 Years
----------	----------------

LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias
32009, Greece

+30 22620 58 121
+30 22620 56 743

info@novaluce.com
www.novaluce.com

